

Challenges in Abstract Interpretation for Software Safety

Patrick Cousot


École normale supérieure, Paris, France

cousot@ens.fr www.di.ens.fr/~cousot

Franco-Japanese Workshop on Security
Keio University, Mita Campus, September 5–7, 2005

ENS

École Normale Supérieure (ENS)



Normale Sup. (ENS)



A few former students: Évariste Galois, Louis Pasteur, ...; Nobel prizes: Claude Cohen-Tannoudji, Pierre-Gilles de Gennes, Gabriel Lippmann, Louis Néel, Jean-Baptiste Perrin, Paul Sabatier, ...; Fields Medal holders: Laurent Schwartz, Jean-

Pierre Serre (1st Abel Prize), René Thom, Alain Connes, Pierre-Louis Lions, Jean-Christophe Yoccoz, Laurent Lafforgue; Fictitious mathematicians: Nicolas Bourbaki; Philosophers: Henri Bergson (Nobel Prize), Louis Althusser, Simone de Beauvoir, Emile Auguste Chartier “Alain”, Raymond Aron, Jean-Paul Sartre, Maurice Merleau-Ponty, Michel Foucault, Jacques Derrida, Bernard-Henri Lévy...; Politicians: Jean Jaurès, Léon Blum, Édouard Herriot, Georges Pompidou, Alain Juppé, Laurent Fabius, Léopold Sédar Senghor,...; Sociologists: Émile Durkheim, Pierre Bourdieu, ...; Writers: Romain Rolland (Nobel Prize), Jean Giraudoux, Charles Péguy, Julien Gracq, ...;

State of Practice in Software Engineering

An example among many others (Matlab code)

```
» h=get(gca,'children');

apple.awt.EventQueueExceptionCaught Throwable : java.lang.ArrayIndexOutOfBoundsException: 2 >= 2
java.lang.ArrayIndexOutOfBoundsException: 2 >= 2
at java.util.Vector.elementAt(Vector.java:431)
at com.mathworks.mde.help.IndexItem.getFilename(IndexItem.java:100)
at com.mathworks.mde.help.Index.getFilenameForLocation(Index.java:706)
at com.mathworks.mde.help.Index.access$3100(Index.java:29)
at com.mathworks.mde.help.Index$IndexMouseMotionAdapter.mouseMoved(Index.java:768)
at java.awt.AWTEventMulticaster.mouseMoved(AWTEventMulticaster.java:272)
at java.awt.AWTEventMulticaster.mouseMoved(AWTEventMulticaster.java:271)
at java.awt.Component.processMouseEvent(Component.java:5211)
at javax.swing.JComponent.processMouseEvent(JComponent.java:2779)
at com.mathworks.mwswing.MJTable.processMouseEvent(MJTable.java:725)
at java.awt.Component.dispatchEvent(Component.java:4967)
at java.awt.Container.dispatchEvent(Container.java:1613)
at java.awt.Component.dispatchEventImpl(Component.java:3681)
at java.awt.Container.dispatchEventImpl(Container.java:1671)
at java.awt.Component.dispatchEvent(Component.java:3543)
at java.awt.LightweightDispatcher.retargetMouseEvent(Container.java:3527)
at java.awt.LightweightDispatcher.processMouseEvent(Container.java:3255)
at java.awt.LightweightDispatcher.dispatchEvent(Container.java:3172)
at java.awt.Container.dispatchEventImpl(Container.java:1657)
at java.awt.Window.dispatchEventImpl(Window.java:1606)
at java.awt.Component.dispatchEvent(Component.java:3543)
at java.awt.EventQueue.dispatchEvent(EventQueue.java:456)
at java.awt.EventDispatchThread.pumpOneEventForHierarchy(EventDispatchThread.java:234)
at java.awt.EventDispatchThread.pumpEventsForHierarchy(EventDispatchThread.java:184)
at java.awt.EventDispatchThread.pumpEvents(EventDispatchThread.java:178)
at java.awt.EventDispatchThread.pumpEvents(EventDispatchThread.java:170)
at java.awt.EventDispatchThread.run(EventDispatchThread.java:100)
```

The software safety challenge for next 10 years

- Present-day software engineering is almost exclusively manual, with very few automated tools;
- Trust and confidence in specifications and software can no longer be entirely based on the development process (e.g. DO178B in aerospace software);
- In complement, quality assurance must be ensured by new design, modeling, checking, verification and certification tools based on the product itself.

Abstract Interpretation

Reference

- [POPL '77] P. Cousot and R. Cousot. Abstract interpretation: a unified lattice model for static analysis of programs by construction or approximation of fixpoints. In *4th ACM POPL*.
- [Thesis '78] P. Cousot. Méthodes itératives de construction et d'approximation de points fixes d'opérateurs monotones sur un treillis, analyse sémantique de programmes. Thèse ès sci. math. Grenoble, march 1978.
- [POPL '79] P. Cousot & R. Cousot. Systematic design of program analysis frameworks. In *6th ACM POPL*.

Syntax of programs

X

variables $X \in \mathbb{X}$

T

types $T \in \mathbb{T}$

E

arithmetic expressions $E \in \mathbb{E}$

B

boolean expressions $B \in \mathbb{B}$

$D ::= T\ X;$

| $T\ X\ ;\ D'$

$C ::= X = E;$

commands $C \in \mathbb{C}$

| while $B\ C'$


| if $B\ C'\$ else C''

| { $C_1 \dots C_n$ }, ($n \geq 0$)

$P ::= D\ C$

program $P \in \mathbb{P}$

Postcondition semantics



States

Values of given type:

$\mathcal{V}[T]$: values of type $T \in \mathbb{T}$

$\mathcal{V}[\text{int}] \stackrel{\text{def}}{=} \{z \in \mathbb{Z} \mid \text{min_int} \leq z \leq \text{max_int}\}$

Program states $\Sigma[P]$ ¹:

$\Sigma[D \ C] \stackrel{\text{def}}{=} \Sigma[D]$

$\Sigma[T \ X ;] \stackrel{\text{def}}{=} \{X\} \mapsto \mathcal{V}[T]$

$\Sigma[T \ X ; D] \stackrel{\text{def}}{=} (\{X\} \mapsto \mathcal{V}[T]) \cup \Sigma[D]$

¹ States $\rho \in \Sigma[P]$ of a program P map program variables X to their values $\rho(X)$

Concrete Semantic Domain of Programs

Concrete semantic domain for reachability properties:

$$\mathcal{D}\llbracket P \rrbracket \stackrel{\text{def}}{=} \wp(\Sigma\llbracket P \rrbracket) \quad \text{sets of states}$$

i.e. program properties where \subseteq is implication, \emptyset is false, \cup is disjunction.

Concrete Reachability Semantics of Programs

$$S[X = E;]R \stackrel{\text{def}}{=} \{\rho[X \leftarrow \mathcal{E}[E]\rho] \mid \rho \in R \cap \text{dom}(E)\}$$

$$\rho[X \leftarrow v](X) \stackrel{\text{def}}{=} v, \quad \rho[X \leftarrow v](Y) \stackrel{\text{def}}{=} \rho(Y)$$

$$S[\text{if } B \ C']R \stackrel{\text{def}}{=} S[C'](\mathcal{B}[B]R) \cup \mathcal{B}[\neg B]R$$

$$\mathcal{B}[B]R \stackrel{\text{def}}{=} \{\rho \in R \cap \text{dom}(B) \mid B \text{ holds in } \rho\}$$

$$S[\text{if } B \ C' \text{ else } C'']R \stackrel{\text{def}}{=} S[C'](\mathcal{B}[B]R) \cup S[C''](\mathcal{B}[\neg B]R)$$

$$S[\text{while } B \ C']R \stackrel{\text{def}}{=} \text{let } \mathcal{W} = \text{lfp}_{\emptyset}^{\subseteq} \lambda \mathcal{X}. R \cup S[C'](\mathcal{B}[B]\mathcal{X}) \\ \text{in } (\mathcal{B}[\neg B]\mathcal{W})$$

$$S[\{\}]R \stackrel{\text{def}}{=} R$$

$$S[\{C_1 \dots C_n\}]R \stackrel{\text{def}}{=} S[C_n] \circ \dots \circ S[C_1] \quad n > 0$$

$$S[D \ C]R \stackrel{\text{def}}{=} S[C](\Sigma[D]) \quad (\text{uninitialized variables})$$

Not computable (undecidability).

Abstract Semantic Domain of Programs

$$\langle \mathcal{D}^\sharp[P], \sqsubseteq, \perp, \sqcup \rangle$$

such that:

$$\langle \mathcal{D}, \subseteq \rangle \xrightleftharpoons[\alpha]{\gamma} \langle \mathcal{D}^\sharp[P], \sqsubseteq \rangle$$

hence $\langle \mathcal{D}^\sharp[P], \sqsubseteq, \perp, \sqcup \rangle$ is a complete lattice such that
 $\perp = \alpha(\emptyset)$ and $\sqcup X = \alpha(\cup \gamma(X))$

Reduced Product of Abstract Domains

To combine abstractions

$$\langle \mathcal{D}, \subseteq \rangle \xrightleftharpoons[\alpha_1]{\gamma_1} \langle \mathcal{D}_1^\sharp, \sqsubseteq_1 \rangle \text{ and } \langle \mathcal{D}, \subseteq \rangle \xrightleftharpoons[\alpha_2]{\gamma_2} \langle \mathcal{D}_2^\sharp, \sqsubseteq_2 \rangle$$

the reduced product is


$$\alpha(X) \stackrel{\text{def}}{=} \sqcap \{ \langle x, y \rangle \mid X \subseteq \gamma_1(X) \wedge X \subseteq \gamma_2(X) \}$$

such that $\sqsubseteq \stackrel{\text{def}}{=} \sqsubseteq_1 \times \sqsubseteq_2$ and

$$\langle \mathcal{D}, \subseteq \rangle \xrightleftharpoons[\alpha]{\gamma_1 \times \gamma_2} \langle \alpha(\mathcal{D}), \sqsubseteq \rangle$$

Example: $x \in [1, 9] \wedge x \bmod 2 = 0$ reduces to $x \in [2, 8] \wedge x \bmod 2 = 0$

Approximate Fixpoint Abstraction




$$F \circ \gamma \sqsubseteq \gamma \circ F^\sharp \Rightarrow \text{lfp } F \sqsubseteq \gamma(\text{lfp } F^\sharp)$$

Abstract Reachability Semantics of Programs

$$\begin{aligned}
 S^\sharp[X = E;]R &\stackrel{\text{def}}{=} \alpha(\{\rho[X \leftarrow \mathcal{E}[E]\rho] \mid \rho \in \gamma(R) \cap \text{dom}(E)\}) \\
 S^\sharp[\text{if } B C']R &\stackrel{\text{def}}{=} S^\sharp[C'](\mathcal{B}^\sharp[B]R) \sqcup \mathcal{B}^\sharp[\neg B]R \\
 \mathcal{B}^\sharp[B]R &\stackrel{\text{def}}{=} \alpha(\{\rho \in \gamma(R) \cap \text{dom}(B) \mid B \text{ holds in } \rho\}) \\
 S^\sharp[\text{if } B C' \text{ else } C'']R &\stackrel{\text{def}}{=} S^\sharp[C'](\mathcal{B}^\sharp[B]R) \sqcup S^\sharp[C''](\mathcal{B}^\sharp[\neg B]R) \\
 S^\sharp[\text{while } B C']R &\stackrel{\text{def}}{=} \text{let } \mathcal{W} = \text{lfp}_\perp^\sqsubseteq \lambda \mathcal{X}. R \sqcup S^\sharp[C'](\mathcal{B}^\sharp[B]\mathcal{X}) \\
 &\quad \text{in } (\mathcal{B}^\sharp[\neg B]\mathcal{W}) \\
 S^\sharp[\{\}]R &\stackrel{\text{def}}{=} R \\
 S^\sharp[\{C_1 \dots C_n\}]R &\stackrel{\text{def}}{=} S^\sharp[C_n] \circ \dots \circ S^\sharp[C_1] \quad n > 0 \\
 S^\sharp[D C]R &\stackrel{\text{def}}{=} S^\sharp[C](\top) \quad (\text{uninitialized variables})
 \end{aligned}$$

Convergence Acceleration with Widening



Abstract Semantics with Convergence Acceleration²

$$\begin{aligned}
 S^\sharp[X = E;]R &\stackrel{\text{def}}{=} \alpha(\{\rho[X \leftarrow \mathcal{E}[E]\rho] \mid \rho \in \gamma(R) \cap \text{dom}(E)\}) \\
 S^\sharp[\text{if } B C']R &\stackrel{\text{def}}{=} S^\sharp[C'](\mathcal{B}^\sharp[B]R) \sqcup \mathcal{B}^\sharp[\neg B]R \\
 \mathcal{B}^\sharp[B]R &\stackrel{\text{def}}{=} \alpha(\{\rho \in \gamma(R) \cap \text{dom}(B) \mid B \text{ holds in } \rho\}) \\
 S^\sharp[\text{if } B C' \text{ else } C'']R &\stackrel{\text{def}}{=} S^\sharp[C'](\mathcal{B}^\sharp[B]R) \sqcup S^\sharp[C''](\mathcal{B}^\sharp[\neg B]R) \\
 S^\sharp[\text{while } B C']R &\stackrel{\text{def}}{=} \text{let } \mathcal{F}^\sharp = \lambda \mathcal{X}. \text{let } \mathcal{Y} = R \sqcup S^\sharp[C'](\mathcal{B}^\sharp[B]\mathcal{X}) \\
 &\quad \text{in if } \mathcal{Y} \sqsubseteq \mathcal{X} \text{ then } \mathcal{X} \text{ else } \mathcal{X} \triangleright \mathcal{Y} \\
 &\quad \text{and } \mathcal{W} = \text{lfp}_\perp^\sqsubseteq \mathcal{F}^\sharp \quad \text{in } (\mathcal{B}^\sharp[\neg B]\mathcal{W}) \\
 S^\sharp[\{\}]R &\stackrel{\text{def}}{=} R \\
 S^\sharp[\{C_1 \dots C_n\}]R &\stackrel{\text{def}}{=} S^\sharp[C_n] \circ \dots \circ S^\sharp[C_1] \quad n > 0 \\
 S^\sharp[D C]R &\stackrel{\text{def}}{=} S^\sharp[C](\top) \quad (\text{uninitialized variables})
 \end{aligned}$$

² Note: \mathcal{F}^\sharp not monotonic!

Applications of Abstract Interpretation

Applications of Abstract Interpretation

- Static Program Analysis [POPL '77], [POPL '78], [POPL '79] including Dataflow Analysis [POPL '79], [POPL '00], Set-based Analysis [FPCA '95], Predicate Abstraction [Manna's festschrift '03], . . .
- Syntax Analysis [TCS 290(1) 2002]
- Hierarchies of Semantics (including Proofs) [POPL '92], [TCS 277(1–2) 2002]
- Typing & Type Inference [POPL '97]

Applications of Abstract Interpretation (Cont'd)

- (Abstract) Model Checking [POPL '00]
- Program Transformation [POPL '02]
- Software Watermarking [POPL '04]
- Bisimulations [RT-ESOP '04]

All these techniques involve sound approximations that can be formalized by abstract interpretation

Static Analysis

-
- Reference —
- [1] P. Cousot and R. Cousot. Static determination of dynamic properties of programs. In *Proceedings of the Second International Symposium on Programming*, pages 106–130. Dunod, Paris, France, 1976.

State of the Art in Automatic Static Program Analysis

Static analysis tools

- Determine automatically from the program text program properties of a certain class that do hold at runtime (e.g. absence of runtime error);
- Based on the automatic computation of machine representable abstractions³ of all possible executions of the program in any possible environment;
- Scales up to hundreds of thousands lines;
- Undecidable whence false alarms are possible⁴

³ sound but (in general) incomplete approximations.

⁴ cases when a question on the program runtime behavior cannot be answered automatically for sure

Degree of specialization

- Specialization for a class of runtime properties (e.g. absence of runtime errors)
 - Specialization for a programming language (e.g. PolySpace Suite for Ada, C or C++)
 - Specialization for a programming style (e.g. C Global Surveyor)
 - Specialization for an application type (e.g. ASTRÉE for embedded real-time synchronous⁵ autocodes)
- ⇒ The more specialized, the less false alarms⁶!


⁵ deterministic

⁶ but the less specialized, the larger commercial market (and the less client satisfaction)!

The ASTRÉE static analyzer (www.astree.ens.fr)


- ASTRÉE is a static program analyzer aiming at proving the absence of Run Time Errors (started Nov. 2001)
- C programs, no dynamic memory allocation and recursion
- Encompass many (automatically generated) synchronous, time-triggered, real-time, safety critical, embedded software
- automotive, energy and aerospace applications
 - ⇒ e.g. No false alarm on the electric flight control codes for the A340 (Nov. 2003) and A380 (Nov. 2004) generated from SAO/SCADE.

2^d Order Digital Filter:




Ellipsoid Abstract Domain for Filters


- Computes $X_n = \begin{cases} \alpha X_{n-1} + \beta X_{n-2} + Y_n \\ I_n \end{cases}$
- The concrete computation is bounded, which must be proved in the abstract.
- There is no stable interval or octagon.
- The simplest stable surface is an ellipsoid.



execution trace



unstable interval



stable ellipsoid

```

typedef enum {FALSE = 0, TRUE = 1} BOOLEAN;
BOOLEAN INIT; float P, X;

void filter () {
    static float E[2], S[2];
    if (INIT) { S[0] = X; P = X; E[0] = X; }
    else { P = (((((0.5 * X) - (E[0] * 0.7)) + (E[1] * 0.4))
                  + (S[0] * 1.5)) - (S[1] * 0.7)); }
    E[1] = E[0]; E[0] = X; S[1] = S[0]; S[0] = P;
    /* S[0], S[1] in [-1327.02698354, 1327.02698354] */
}

void main () { X = 0.2 * X + 5; INIT = TRUE;
    while (1) {
        X = 0.9 * X + 35; /* simulated filter input */
        filter (); INIT = FALSE; }
}

```

Filter Example

Reference

see <http://www.astree.ens.fr/>

Arithmetic-geometric progressions

- Abstract domain: $(\mathbb{R}^+)^5$ ⁷
- Concretization (any function bounded by the arithmetic-geometric progression):

$$\gamma \in (\mathbb{R}^+)^5 \mapsto \wp(\mathbb{N} \mapsto \mathbb{R})$$

$$\gamma(M, a, b, a', b') =$$

$$\{f \mid \forall k \in \mathbb{N} : |f(k)| \leq (\lambda x \cdot ax + b \circ (\lambda x \cdot a'x + b')^k)(M)\}$$

Reference

see <http://www.astree.ens.fr/>

⁷ here in \mathbb{R}

Arithmetic-Geometric Progressions (Example 1)

```
% cat count.c
typedef enum {FALSE = 0, TRUE = 1} BOOLEAN;
volatile BOOLEAN I; int R; BOOLEAN T;
void main() {

    R = 0;
    while (TRUE) {
        __ASTREE_log_vars((R));
        if (I) { R = R + 1; }           ← potential overflow!
        else { R = 0; }
        T = (R >= 100);
        __ASTREE_wait_for_clock();
    }
}

% cat count.config
__ASTREE_volatile_input((I [0,1]));
__ASTREE_max_clock((3600000));
% astree -exec-fn main -config-sem count.config count.c|grep '|R|'
|R| <= 0. + clock *1. <= 3600001.
```

Arithmetic-geometric progressions (Example 2)

```
% cat retro.c
typedef enum {FALSE=0, TRUE=1} BOOL;
BOOL FIRST;
volatile BOOL SWITCH;
volatile float E;
float P, X, A, B;

void dev( )
{ X=E;
  if (FIRST) { P = X; }
  else
    { P = (P - (((2.0 * P) - A) - B)
           * 4.491048e-03)); }
  B = A;
  if (SWITCH) {A = P;}
  else {A = X;}
}
```

```
void main()
{ FIRST = TRUE;
  while (TRUE) {
    dev( );
    FIRST = FALSE;
    __ASTREE_wait_for_clock();
  }
}


% cat retro.config
__ASTREE_volatile_input((E [-15.0, 15.0]));
__ASTREE_volatile_input((SWITCH [0,1]));
__ASTREE_max_clock((3600000));
|P| <= (15. + 5.87747175411e-39
/ 1.19209290217e-07) * (1
+ 1.19209290217e-07)^clock
- 5.87747175411e-39 /
1.19209290217e-07 <=
23.0393526881
```

Towards System Verification Tools


Reference

- [2] P. Cousot. Proving Program Invariance and Termination by Parametric Abstraction, Lagrangian Relaxation and Semidefinite Programming, invited paper. In *Sixth International Conference on Verification, Model Checking and Abstract Interpretation (VMCAI'05)*, pages 1–24, Paris, France, January 17-19, 2005. Lecture Notes in Computer Science, volume 3385, Springer, Berlin.
- [APLAS'06] P. Cousot. Integrating Physical Systems in the Static Analysis of Embedded Control Software., invited talk In *APLAS'06*, Tokyo, Nov. 2005, to appear (LNCS).

Computer controlled systems




Software test



Abstractions: program → none, system → precise

- Very expensive
- Not exhaustive
- Extended during flight test period
- Late discovery of errors can delay the program by months
(the whole software development process must be rechecked)

Software analysis & verification with ASTRÉE




Abstractions: program → precise, system → coarse

- Exhaustive
- Can be made precise by specialization⁸ to get no false alarm
- No specification of the controlled system (but for ranges of values of a few sensors)
- Impossible to prove essential properties of the controlled system (e.g. controlability, robustness, stability)

⁸ To specific families of properties and programs

System analysis & verification by control engineers




Abstractions: program → imprecise, system → precise

- The controller model is a rough abstraction of the control program:
 - Continuous, not discrete
 - Limited to control laws
 - Does not take into account fault-tolerance to failures and computer-related system dependability.
- In theory, SDP-based search of system invariants (Lyapunov-like functions) can be used to prove reachability and inevitability properties
- Problems to scale up (e.g. over long periods of time)
- In practice, the system/controller model is explored by discrete simulations (testing)

Exploring new avenues in static analysis


System analysis & verification, Avenue 1



Abstractions: program → precise, system → precise

- Exhaustive (contrary to current simulations)
- Traditional abstractions (e.g. polyhedral abstraction with widening) seem to be too imprecise
- Currently exploring new abstractions (issued from control theory like ellipsoidal calculus using SDP)
- Prototype implementation in construction!

System analysis & verification, Avenue 2




Abstractions: program → precise, system → precise

- Example of invariant translation: ellipsoidal \longrightarrow polyhedral⁹
- The static analysis is easier on the system/controller model using continuous optimization methods
- The translated invariants can be checked for the system simulator/control program (easier than invariant discovery)
- Should scale up since these complex invariants are relevant to a small part of the control program only

⁹ For which floating point computations can be taken into account

System analysis & verification, Avenue 3



Abstractions: program → precise, system → precise

- The invariant hypotheses on the controlled system are assumed to be true
- It remains to perform the control program analysis under these hypothesis
- The results can then be checked on the whole system (as in case 2, but now using refined invariants on the control program!)
- Iterating this process leads to *static analysis by refinement of specifications*

Conclusion

Scientific and technologic objective

To develop formal tools to answer questions about software:

- from control model design to software implementation,
- for a wide range of design and software properties, which would be general enough to benefit all software-intensive industries, and can be adapted to specific application domains.

THE END, THANK YOU

More references at URL www.di.ens.fr/~cousot
www.astree.ens.fr.

References

- [3] www.astree.ens.fr [5, 6, 7, 8, 9, 10, 11, 12]
- [4] P. Cousot. *Méthodes itératives de construction et d'approximation de points fixes d'opérateurs monotones sur un treillis, analyse sémantique de programmes.* Thèse d'État ès sciences mathématiques, Université scientifique et médicale de Grenoble, Grenoble, France, 21 March 1978.
- [5] B. Blanchet, P. Cousot, R. Cousot, J. Feret, L. Mauborgne, A. Miné, D. Monniaux, and X. Rival. [Design and implementation of a special-purpose static program analyzer for safety-critical real-time embedded software](#). *The Essence of Computation: Complexity, Analysis, Transformation. Essays Dedicated to Neil D. Jones*, LNCS 2566, pp. 85–108. Springer, 2002.
- [6] B. Blanchet, P. Cousot, R. Cousot, J. Feret, L. Mauborgne, A. Miné, D. Monniaux, and X. Rival. [A static analyzer for large safety-critical software](#). *PLDI'03*, San Diego, pp. 196–207, ACM Press, 2003.
- [POPL '77] P. Cousot and R. Cousot. [Abstract interpretation: a unified lattice model for static analysis of programs by construction or approximation of fixpoints](#). In *Conference Record of the Fourth Annual ACM SIGPLAN-SIGACT Symposium on Principles of Programming Languages*, pages 238–252, Los Angeles, California, 1977. ACM Press, New York, NY, USA.
- [PACJM '79] P. Cousot and R. Cousot. [Constructive versions of Tarski's fixed point theorems](#). *Pacific Journal of Mathematics* 82(1):43–57 (1979).
- [POPL '78] P. Cousot and N. Halbwachs. [Automatic discovery of linear restraints among variables of a program](#). In *Conference Record of the Fifth Annual ACM SIGPLAN-SIGACT Symposium on Principles of Programming Languages*, pages 84–97, Tucson, Arizona, 1978. ACM Press, New York, NY, U.S.A.

- [POPL '79] P. Cousot and R. Cousot. *Systematic design of program analysis frameworks*. In *Conference Record of the Sixth Annual ACM SIGPLAN-SIGACT Symposium on Principles of Programming Languages*, pages 269–282, San Antonio, Texas, 1979. ACM Press, New York, NY, U.S.A.
- [POPL '92] P. Cousot and R. Cousot. *Inductive Definitions, Semantics and Abstract Interpretation*. In *Conference Record of the 19th ACM SIGACT-SIGMOD-SIGART Symposium on Principles of Programming Languages*, pages 83–94, Albuquerque, New Mexico, 1992. ACM Press, New York, U.S.A.
- [FPCA '95] P. Cousot and R. Cousot. *Formal Language, Grammar and Set-Constraint-Based Program Analysis by Abstract Interpretation*. In *SIGPLAN/SIGARCH/WG2.8 7th Conference on Functional Programming and Computer Architecture, FPCA'95*. La Jolla, California, U.S.A., pages 170–181. ACM Press, New York, U.S.A., 25-28 June 1995.
- [POPL '97] P. Cousot. *Types as Abstract Interpretations*. In *Conference Record of the 24th ACM SIGACT-SIGMOD-SIGART Symposium on Principles of Programming Languages*, pages 316–331, Paris, France, 1997. ACM Press, New York, U.S.A.
- [POPL '00] P. Cousot and R. Cousot. *Temporal abstract interpretation*. In *Conference Record of the Twentyseventh Annual ACM SIGPLAN-SIGACT Symposium on Principles of Programming Languages*, pages 12–25, Boston, Mass., January 2000. ACM Press, New York, NY.
- [POPL '02] P. Cousot and R. Cousot. *Systematic Design of Program Transformation Frameworks by Abstract Interpretation*. In *Conference Record of the Twentyninth Annual ACM SIGPLAN-SIGACT Symposium on Principles of Programming Languages*, pages 178–190, Portland, Oregon, January 2002. ACM Press, New York, NY.
- [TCS 277(1–2) 2002] P. Cousot. *Constructive Design of a Hierarchy of Semantics of a Transition System by Abstract Interpretation*. *Theoretical Computer Science* 277(1–2):47–103, 2002.

- [TCS 290(1) 2002] P. Cousot and R. Cousot. Parsing as abstract interpretation of grammar semantics. *Theoret. Comput. Sci.*, 290:531–544, 2003.
- [Manna's festschrift '03] P. Cousot. Verification by Abstract Interpretation. *Proc. Int. Symp. on Verification – Theory & Practice – Honoring Zohar Manna's 64th Birthday*, N. Dershowitz (Ed.), Taormina, Italy, June 29 – July 4, 2003. Lecture Notes in Computer Science, vol. 2772, pp. 243–268. © Springer-Verlag, Berlin, Germany, 2003.
- [7] P. Cousot, R. Cousot, J. Feret, L. Mauborgne, A. Miné, D. Monniaux, and X. Rival. The ASTRÉE analyser. *ESOP 2005*, Edinburgh, LNCS 3444, pp. 21–30, Springer, 2005.
- [8] J. Feret. Static analysis of digital filters. *ESOP'04*, Barcelona, LNCS 2986, pp. 33—48, Springer, 2004.
- [9] J. Feret. The arithmetic-geometric progression abstract domain. In *VMCAI'05*, Paris, LNCS 3385, pp. 42–58, Springer, 2005.
- [10] Laurent Mauborgne & Xavier Rival. Trace Partitioning in Abstract Interpretation Based Static Analyzers. *ESOP'05*, Edinburgh, LNCS 3444, pp. 5–20, Springer, 2005.
- [11] A. Miné. A New Numerical Abstract Domain Based on Difference-Bound Matrices. *PADO'2001*, LNCS 2053, Springer, 2001, pp. 155–172.
- [12] A. Miné. Relational abstract domains for the detection of floating-point run-time errors. *ESOP'04*, Barcelona, LNCS 2986, pp. 3—17, Springer, 2004.
- [POPL '04] P. Cousot and R. Cousot. An Abstract Interpretation-Based Framework for Software Watermarking. In *Conference Record of the Thirtyfirst Annual ACM SIGPLAN-SIGACT Symposium on Principles of Programming Languages*, pages 173–185, Venice, Italy, January 14-16, 2004. ACM Press, New York, NY.

[DPG-ICALP '05] M. Dalla Preda and R. Giacobazzi. Semantic-based Code Obfuscation by Abstract Interpretation. In Proc. 32nd Int. Colloquium on Automata, Languages and Programming (ICALP'05 – Track B). LNCS, 2005 Springer-Verlag. July 11-15, 2005, Lisboa, Portugal. To appear.

[EMSOFT '01] C. Ferdinand, R. Heckmann, M. Langenbach, F. Martin, M. Schmidt, H. Theiling, S. Thesing, and R. Wilhelm. Reliable and precise WCET determination for a real-life processor. *ESOP (2001)*, LNCS 2211, 469–485.

[RT-ESOP '04] F. Ranzato and F. Tapparo. Strong Preservation as Completeness in Abstract Interpretation. ESOP 2004, Barcelona, Spain, March 29 - April 2, 2004, D.A. Schmidt (Ed), LNCS 2986, Springer, 2004, pp. 18–32.