

« Program Termination Proof by Parametric Abstraction and Semi-definite Programming »

Patrick Cousot

École normale supérieure, Paris

cousot@ens.fr www.di.ens.fr/~cousot

Seminar, Department of Computing and Information Sciences,
Kansas State University, Manhattan, KS, September 6, 2006



Sep. 6, 2006

— 1 —

© P. Cousot



Reference

- [1] P. Cousot. – Proving Program Invariance and Termination by Parametric Abstraction, Lagrangian Relaxation and Semidefinite Programming.
In : Proc. Sixth Int. Conf. on Verification, Model Checking and Abstract Interpretation (VMCAI 2005), R. Cousot (Ed.), Paris, France, 17–19 Jan. 2005. pp. 1–24. – Lecture Notes In Computer Science 3385, Springer.



Static analysis



Principle of static analysis

- Define the most precise program property as a fixpoint
 $\text{Ifp } F$
- Effectively compute a fixpoint approximation:
 - iteration-based fixpoint approximation
 - constraint-based fixpoint approximation



Iteration-based static analysis

- Effectively overapproximate the iterative fixpoint definition¹:

$$\text{Ifp } F = \bigsqcup_{\lambda \in \mathbb{O}} X^\lambda$$

$$X^0 = \perp$$
$$X^\lambda = \bigsqcup_{\eta < \lambda} F(X^\eta)$$

¹ under Tarski's fixpoint theorem hypotheses



Constraint-based static analysis

- Effectively solve a postfixpoint constraint:

$$\text{Ifp } F = \bigcap \{X \mid F(X) \sqsubseteq X\}$$

since $F(X) \sqsubseteq X$ implies $\text{Ifp } F \sqsubseteq X$

- Sometimes, the constraint resolution algorithm is nothing but the iterative computation of $\text{Ifp } F$ ²
- Constraint-based static analysis is the main subject of this talk.

² An example is set-based analysis as shown in Patrick Cousot & Radhia Cousot. *Formal Language, Grammar and Set-Constraint-Based Program Analysis by Abstract Interpretation*. In Conference Record of FPCA '95 ACM Conference on Functional Programming and Computer Architecture, pages 170–181, La Jolla, California, U.S.A., 25-28 June 1995.



Parametric abstraction

- Parametric abstract domain: $X \in \{f(a) \mid a \in \Delta\}$, a is an unknown parameter
- Verification condition: X satisfies $F(X) \sqsubseteq X$ if [and only if] $\exists a \in \Delta : F(f(a)) \sqsubseteq f(a)$ that is $\exists a : C_F(a)$ where $C_F \in \Delta \mapsto \mathbb{B}$ are constraints over the unknown parameter a



Fixpoint versus Constraint-based Approach for Termination Analysis

1. Termination can be expressed in fixpoint form³
2. However we know no effective fixpoint underapproximation method needed to overestimation the termination rank
3. So we consider a constraint-based approach abstracting Floyd's ranking function method


³ See Sect. 11.2 of Patrick Cousot. *Constructive Design of a hierarchy of Semantics of a Transition System by Abstract Interpretation*. *Theoret. Comput. Sci.* 277(1–2):47–103, 2002. © Elsevier Science.



Overview of the Termination Analysis Method



Proving Termination of a Loop



The main point in this talk is (4).



Proving Termination of a Loop

1. Perform an iterated forward/backward relational static analysis of the loop with *termination hypothesis* to determine a *necessary proper termination precondition*
2. Assuming the *termination precondition*, perform an forward relational static analysis of the loop to determine the *loop invariant*
3. Assuming the loop invariant, perform an forward relational static analysis of the loop body to determine the *loop abstract operational semantics*
4. Assuming the loop semantics, use an abstraction of Floyd's ranking function method to prove termination of the loop



Arithmetic Mean Example

```
while (x <> y) do
    x := x - 1;
    y := y + 1
od
```

The polyhedral abstraction used for the static analysis of the examples is implemented using Bertrand Jeannet's NewPolka library.




Arithmetic Mean Example

1. Perform an **iterated forward/backward relational static analysis** of the loop with *termination hypothesis* to determine a *necessary proper termination precondition*
2. Assuming the *termination precondition*, perform an **forward relational static analysis** of the loop to determine the **loop invariant**
3. Assuming the **loop invariant**, perform an **forward relational static analysis** of the loop body to determine the **loop abstract operational semantics**
4. Assuming the **loop semantics**, use an **abstraction** of Floyd's ranking function method to **prove termination** of the loop





Forward/reachability properties



Example: **partial correctness** (must stay into safe states)




Backward/ancestry properties



Example: **termination** (must reach final states)

Forward/backward properties



Example: total correctness (stay safe while reaching final states)

Principle of the iterated forward/backward iteration-based approximate analysis

- Overapproximate

$$\text{Ifp } F \sqcap \text{Ifp } B$$

by overapproximations of the decreasing sequence

$$X^0 = \top$$

...

$$X^{2n+1} = \text{Ifp } \lambda Y . X^{2n} \sqcap F(Y)$$

$$X^{2n+2} = \text{Ifp } \lambda Y . X^{2n+1} \sqcap B(Y)$$

...



Arithmetic Mean Example: Termination Precondition (1)

```
{x>=y}
while (x <> y) do
  {x>=y+2}
    x := x - 1;
  {x>=y+1}
    y := y + 1
  {x>=y}
od
{x=y}
```



Idea 1

The auxiliary termination counter method



Arithmetic Mean Example: Termination Precondition (2)

```
{x=y+2k,x>=y}
while (x <> y) do
  {x=y+2k ,x>=y+2}
    k := k - 1;
  {x=y+2k+2 ,x>=y+2}
    x := x - 1;
  {x=y+2k+1 ,x>=y+1}
    y := y + 1
  {x=y+2k ,x>=y}
od
{x=y ,k=0}
assume (k = 0)
{x=y ,k=0}
```

Add an auxiliary termination counter to enforce (bounded) termination in the backward analysis!



Arithmetic Mean Example

1. Perform an iterated forward/backward relational static analysis of the loop with *termination hypothesis* to determine a *necessary proper termination precondition*
2. Assuming the *termination precondition*, perform an **forward relational static analysis** of the loop to determine the **loop invariant**
3. Assuming the loop invariant, perform an **forward relational static analysis** of the loop body to determine the **loop abstract operational semantics**
4. Assuming the loop semantics, use an **abstraction** of Floyd's ranking function method to **prove termination** of the loop



Arithmetic Mean Example: Loop Invariant

```
assume ((x=y+2*k) & (x>=y));
{x=y+2k,x>=y}
while (x <> y) do
  {x=y+2k,x>=y+2}
    k := k - 1;
  {x=y+2k+2,x>=y+2}
    x := x - 1;
  {x=y+2k+1,x>=y+1}
    y := y + 1
  {x=y+2k,x>=y}
od
{k=0,x=y}
```



Arithmetic Mean Example

1. Perform an iterated forward/backward relational static analysis of the loop with *termination hypothesis* to determine a *necessary proper termination precondition*
2. Assuming the *termination precondition*, perform an forward relational static analysis of the loop to determine the *loop invariant*
3. Assuming the loop invariant, perform an *forward relational static analysis* of the loop body to determine the *loop abstract operational semantics*
4. Assuming the loop semantics, use an *abstraction* of Floyd's ranking function method to *prove termination* of the loop



Arithmetic Mean Example: Body Relational Semantics

Case $x < y$:

```
assume (x=y+2*k)&(x>=y+2);  
{x=y+2k, x>=y+2}  
assume (x < y);  
empty(6)  
assume (x0=x)&(y0=y)&(k0=k);  
empty(6)  
k := k - 1;  
x := x - 1;  
y := y + 1  
empty(6)
```

Case $x > y$:

```
assume (x=y+2*k)&(x>=y+2);  
{x=y+2k, x>=y+2}  
assume (x > y);  
{x=y+2k, x>=y+2}  
assume (x0=x)&(y0=y)&(k0=k);  
{x=y+2k0, y=y0, x=x0, x=y+2k,  
x>=y+2}  
k := k - 1;  
x := x - 1;  
y := y + 1  
{x+2=y+2k0, y=y0+1, x+1=x0,  
x=y+2k, x>=y}
```



Arithmetic Mean Example

1. Perform an iterated forward/backward relational static analysis of the loop with *termination hypothesis* to determine a *necessary proper termination precondition*
2. Assuming the *termination precondition*, perform an forward relational static analysis of the loop to determine the *loop invariant*
3. Assuming the loop invariant, perform an forward relational static analysis of the loop body to determine the *loop abstract operational semantics*
4. Assuming the loop semantics, use an *abstraction* of Floyd's ranking function method to *prove termination* of the loop



Floyd's method for termination of while B do C

Given a loop invariant I , find an $\mathbb{R}/\mathbb{Q}/\mathbb{Z}$ -valued unknown rank function r such that:

- The rank is *nonnegative*:

$$\forall x_0, x : I(x_0) \wedge \llbracket B; C \rrbracket(x_0, x) \Rightarrow r(x_0) \geq 0$$

- The rank is *strictly decreasing*:

$$\forall x_0, x : I(x_0) \wedge \llbracket B; C \rrbracket(x_0, x) \Rightarrow r(x) \leq r(x_0) - \eta$$

$\eta \geq 1$ for \mathbb{Z} , $\eta > 0$ for \mathbb{R}/\mathbb{Q} to avoid Zeno $\frac{1}{2}, \frac{1}{4}, \frac{1}{8}, \dots$



Problems

- How to get rid of the implication \Rightarrow ?
→ Lagrangian relaxation
- How to get rid of the universal quantification \forall ?
→ Quantifier elimination/mathematical programming & relaxation



Algorithmically interesting cases

- linear inequalities
 - linear programming
- linear matrix inequalities (LMI)/quadratic forms
 - semidefinite programming
- semialgebraic sets
 - polynomial quantifier elimination, or
 - relaxation with semidefinite programming



```

» clear all;
[v0,v] = variables('x','y','k')
% linear inequalities
%
%      x0 y0 k0
Ai = [ 0 0 0];
%
%      x  y  k
Ai_ = [ 1 -1 0]; % x0 - y0 >= 0
bi = [0];
[N Mk(:,:, :)]=linToMk(Ai,Ai_,bi);
%
% linear equalities
%
%      x0 y0 k0
Ae = [ 0 0 -2;
        0 -1 0;
        -1 0 0;
        0 0 0];
%
%      x  y  k
Ae_ = [ 1 -1 0; % x - y - 2*k0 - 2 = 0
        0 1 0; % y - y0 - 1 = 0
        1 0 0; % x - x0 + 1 = 0
        1 -1 -2]; % x - y - 2*k = 0
be = [2; -1; 1; 0];
[M Mk(:,:,N+1:N+M)]=linToMk(Ae,Ae_,be);

```

Arithmetic Mean Example: Ranking Function with Semi-definite Programming Relaxation

Input the loop abstract semantics



```
» display_Mk(Mk, N, v0, v);
```

...

```
+1.x -1.y >= 0  
-2.k0 +1.x -1.y +2 = 0  
-1.y0 +1.y -1 = 0  
-1.x0 +1.x +1 = 0  
+1.x -1.y -2.k = 0
```

...

```
» [diagnostic,R] = termination(v0, v, Mk, N, 'integer', 'linear');  
» disp(diagnostic)  
    feasible (bnb)  
» intrank(R, v)
```

$$r(x, y, k) = +4 \cdot k - 2$$

- Display the abstract semantics of the loop while B do C
- compute ranking function, if any



Quantifier Elimination



Quantifier elimination (Tarski-Seidenberg)

- quantifier elimination for the first-order theory of real closed fields:
 - F is a logical combination of polynomial equations and inequalities in the variables x_1, \dots, x_n
 - Tarski-Seidenberg decision procedure
 - transforms a formula*
$$\forall/\exists x_1 : \dots \forall/\exists x_n : F(x_1, \dots, x_n)$$
into an equivalent quantifier free formula
- cannot be bound by any tower of exponentials [Heintz, Roy, Solerno 89]



Quantifier elimination (Collins)

- cylindrical algebraic decomposition method by Collins
- implemented in MATHEMATICA[®]
- worst-case time-complexity for real quantifier elimination is “only” doubly exponential in the number of quantifier blocks
- Various optimisations and heuristics can be used⁴

⁴ See e.g. REDLOG <http://www.fmi.uni-passau.de/~redlog/>



Scaling up

However

- does not scale up beyond a few variables!
- too bad!



Proving Termination by Parametric Abstraction, Lagrangian Relaxation and Semidefinite Programming



Idea 2

Express the loop invariant and relational semantics
as numerical positivity constraints



Relational semantics of while B do C od loops

- $x_0 \in \mathbb{R}/\mathbb{Q}/\mathbb{Z}$: values of the loop variables *before* a loop iteration
- $x \in \mathbb{R}/\mathbb{Q}/\mathbb{Z}$: values of the loop variables *after* a loop iteration
- $I(x_0)$: loop invariant, $\llbracket B; C \rrbracket(x_0, x)$: relational semantics of *one iteration of the loop body*
- $I(x_0) \wedge \llbracket B; C \rrbracket(x_0, x) = \bigwedge_{i=1}^N \sigma_i(x_0, x) \geq_i 0 \quad (\geq_i \in \{>, \geq, =\})$
- not a restriction for numerical programs



Example of linear program (Arithmetic mean)

$$[A \ A'][x_0 \ x]^T \geq b$$

```
{x=y+2k, x>=y}
while (x <> y) do
    k := k - 1;
    x := x - 1;
    y := y + 1
od
```

$$\begin{aligned} +1.x - 1.y &\geq 0 \\ -2.k0 + 1.x - 1.y + 2 &= 0 \\ -1.y0 + 1.y - 1 &= 0 \\ -1.x0 + 1.x + 1 &= 0 \\ +1.x - 1.y - 2.k &= 0 \end{aligned}$$

$$\left[\begin{array}{ccc|ccc} 0 & 0 & 0 & 1 & -1 & 0 \\ 0 & 0 & -2 & 1 & -1 & 0 \\ 0 & -1 & 0 & 0 & 1 & 0 \\ -1 & 0 & 0 & 1 & 0 & 0 \\ 0 & 0 & 0 & 1 & -1 & -2 \end{array} \right] \begin{bmatrix} x_0 \\ y_0 \\ k_0 \\ x \\ y \\ k \end{bmatrix} \geq \begin{bmatrix} 0 \\ -2 \\ 1 \\ -1 \\ 0 \end{bmatrix}$$



Example of quadratic form program (factorial)

$$[x \ x'] A [x \ x']^\top + 2[x \ x'] q + r \geq 0$$

```

n := 0;                                -1.f0 +1.N0 >= 0
f := 1;                                 +1.n0 >= 0
while (f <= N) do
    n := n + 1;                         +1.f0 -1 >= 0
    f := n * f                           -1.n0 +1.n -1 = 0
od                                         +1.N0 -1.N = 0
                                            -1.f0.n +1.f = 0


```

$$[n_0 \ f_0 \ N_0 \ n \ f \ N] \begin{bmatrix} 0 & 0 & 0 & 0 & 0 & 0 \\ 0 & 0 & 0 & -\frac{1}{2} & 0 & 0 \\ 0 & 0 & 0 & 0 & 0 & 0 \\ 0 & -\frac{1}{2} & 0 & 0 & 0 & 0 \\ 0 & 0 & 0 & 0 & 0 & 0 \\ 0 & 0 & 0 & 0 & 0 & 0 \end{bmatrix} \begin{bmatrix} n_0 \\ f_0 \\ N_0 \\ n \\ f \\ N \end{bmatrix} + 2[n_0 \ f_0 \ N_0 \ n \ f \ N] \begin{bmatrix} 0 \\ 0 \\ 0 \\ 0 \\ \frac{1}{2} \\ 0 \end{bmatrix} + 0 = 0$$



Example of semialgebraic program (logistic map)

```
eps = 1.0e-9;  
while (0 <= a) & (a <= 1 - eps)  
    & (eps <= x) & (x <= 1) do  
    x := a*x*(1-x)  
od
```



Floyd's method for termination of while B do C

Find an $\mathbb{R}/\mathbb{Q}/\mathbb{Z}$ -valued unknown rank function r and $\eta > 0$ such that:

- The rank is *nonnegative*:

$$\forall x_0, x : \bigwedge_{i=1}^N \sigma_i(x_0, x) \geq_i 0 \Rightarrow r(x_0) \geq 0$$

- The rank is *strictly decreasing*:

$$\forall x_0, x : \bigwedge_{i=1}^N \sigma_i(x_0, x) \geq_i 0 \Rightarrow r(x_0) - r(x) - \eta \geq 0$$




Idea 3

Eliminate the conjunction \wedge and implication \Rightarrow by
Lagrangian relaxation




Implication (general case)



$$\begin{aligned} A \Rightarrow B \\ \Leftrightarrow \\ \forall x \in A : x \in B \end{aligned}$$



Implication (linear case)



$$A \Rightarrow B$$


(assuming $A \neq \emptyset$)

\Leftarrow (soundness)

\Rightarrow (completeness)

border of A parallel to border of B

Lagrangian relaxation (linear case)



Lagrangian relaxation, formally

Let \mathbb{V} be a finite dimensional linear vector space, $N > 0$ and $\forall k \in [0, N] : \sigma_k \in \mathbb{V} \mapsto \mathbb{R}$.

$$\forall x \in \mathbb{V} : \left(\bigwedge_{k=1}^N \sigma_k(x) \geq 0 \right) \Rightarrow (\sigma_0(x) \geq 0)$$

- \Leftarrow soundness (Lagrange)
- \Rightarrow completeness (lossless)
- $\not\Rightarrow$ incompleteness (lossy)

$$\exists \lambda \in [1, N] \mapsto \mathbb{R}^+ : \forall x \in \mathbb{V} : \sigma_0(x) - \sum_{k=1}^N \lambda_k \sigma_k(x) \geq 0$$

relaxation = approximation, λ_i = Lagrange coefficients



Lagrangian relaxation, equality constraints

$$\forall x \in \mathbb{V} : \left(\bigwedge_{k=1}^N \sigma_k(x) = 0 \right) \Rightarrow (\sigma_0(x) \geq 0)$$

\Leftarrow soundness (Lagrange)

$$\exists \lambda \in [1, N] \mapsto \mathbb{R}^+ : \forall x \in \mathbb{V} : \sigma_0(x) - \sum_{k=1}^N \lambda_k \sigma_k(x) \geq 0$$

$$\wedge \exists \lambda' \in [1, N] \mapsto \mathbb{R}^+ : \forall x \in \mathbb{V} : \sigma_0(x) + \sum_{k=1}^N \lambda'_k \sigma_k(x) \geq 0$$


$$\Leftrightarrow (\lambda'' = \frac{\lambda' - \lambda}{2})$$

$$\exists \lambda'' \in [1, N] \mapsto \mathbb{R} : \forall x \in \mathbb{V} : \sigma_0(x) - \sum_{k=1}^N \lambda''_k \sigma_k(x) \geq 0$$



Example: affine Farkas' lemma, informally

- An application of Lagrangian relaxation to the case when A is a polyhedron



Example: affine Farkas' lemma, formally

- Formally, if the system $Ax + b \geq 0$ is feasible then

$$\forall x : Ax + b \geq 0 \Rightarrow cx + d \geq 0$$

\Leftarrow (soundness, Lagrange)


\Rightarrow (completeness, Farkas)

$$\exists \lambda \geq 0 : \forall x : cx + d - \lambda(Ax + b) \geq 0 .$$




Yakubovich's S-procedure, informally

- An application of Lagrangian relaxation to the case when A is a quadratic form



Incompleteness (convex case)



Yakubovich's S-procedure, completeness cases

- The constraint $\sigma(x) \geq 0$ is *regular* if and only if $\exists \xi \in \mathbb{V} : \sigma(\xi) > 0$.
- The S-procedure is lossless in the case of one regular quadratic constraint:

$$\begin{aligned}\forall x \in \mathbb{R}^n : x^\top P_1 x + 2q_1^\top x + r_1 \geq 0 \Rightarrow \\ x^\top P_0 x + 2q_0^\top x + r_0 \geq 0\end{aligned}$$

\Leftarrow (Lagrange)

\Rightarrow (Yakubovich)

$$\exists \lambda \geq 0 : \forall x \in \mathbb{R}^n : x^\top \left(\begin{bmatrix} P_0 & q_0 \\ q_0^\top & r_0 \end{bmatrix} - \lambda \begin{bmatrix} P_1 & q_1 \\ q_1^\top & r_1 \end{bmatrix} \right) x \geq 0.$$



Floyd's method for termination of while B do C

Find an $\mathbb{R}/\mathbb{Q}/\mathbb{Z}$ -valued unknown rank function r which is:

- Nonnegative: $\exists \lambda \in [1, N] \mapsto \mathbb{R}^{+ i} :$

$$\forall x_0, x : r(x_0) - \sum_{i=1}^N \lambda_i \sigma_i(x_0, x) \geq 0$$

- Strictly decreasing: $\exists \eta > 0 : \exists \lambda' \in [1, N] \mapsto \mathbb{R}^{+ i} :$

$$\forall x_0, x : (r(x_0) - r(x) - \eta) - \sum_{i=1}^N \lambda'_i \sigma_i(x_0, x) \geq 0$$



Idea 4

Parametric abstraction of the ranking function r



Parametric abstraction

- How can we compute the ranking function r ?
→ parametric abstraction:
 1. Fix the form r_a of the function r a priori, in term of unkown parameters a
 2. Compute the parameters a numerically
- Examples:

$$r_a(x) = a \cdot x^\top$$

linear

$$r_a(x) = a \cdot (x - 1)^\top$$

affine

$$r_a(x) = (x - 1) \cdot a \cdot (x - 1)^\top$$

quadratic



Floyd's method for termination of while B do C

Find $\mathbb{R}/\mathbb{Q}/\mathbb{Z}$ -valued unkown parameters a , such that:

- Nonnegative: $\exists \lambda \in [1, N] \mapsto \mathbb{R}^{+ i} :$

$$\forall x_0, x : r_a(x_0) - \sum_{i=1}^N \lambda_i \sigma_i(x_0, x) \geq 0$$

- Strictly decreasing: $\exists \eta > 0 : \exists \lambda' \in [1, N] \mapsto \mathbb{R}^{+ i} :$

$$\forall x_0, x : (r_a(x_0) - r_a(x) - \eta) - \sum_{i=1}^N \lambda'_i \sigma_i(x_0, x) \geq 0$$



Idea 5

Eliminate the universal quantification \forall using
linear matrix inequalities (LMIs)



Mathematical programming

$$\exists x \in \mathbb{R}^n : \bigwedge_{i=1}^N g_i(x) \geq 0$$

[Minimizing $f(x)$]

feasibility problem : find a solution to the constraints

optimization problem : find a solution, minimizing $f(x)$

Example: Linear programming

$$\exists x \in \mathbb{R}^n : Ax \geq b$$

[Minimizing cx]



Feasibility

- feasibility problem: find a solution $s \in \mathbb{R}^n$ to the optimization program, such that $\bigwedge_{i=1}^N g_i(s) \geq 0$, or to determine that the problem is *infeasible*
- feasible set: $\{x \mid \bigwedge_{i=1}^N g_i(x) \geq 0\}$
- a feasibility problem can be converted into the optimization program

$$m \in \{-y \in \mathbb{R} \mid \bigwedge_{i=1}^N g_i(x) - y \geq 0\}$$



Semidefinite programming

$$\exists x \in \mathbb{R}^n: \quad M(x) \succcurlyeq 0$$

[Minimizing $c x$]

Where the linear matrix inequality (LMI) is

$$M(x) = M_0 + \sum_{k=1}^n x_k M_k$$

with symmetric matrices ($M_k = M_k^\top$) and the positive semidefiniteness is

$$M(x) \succcurlyeq 0 = \forall X \in \mathbb{R}^N : X^\top M(x) X \geq 0$$



Semidefinite programming, once again

Feasibility is:

$$\exists x \in \mathbb{R}^n : \forall X \in \mathbb{R}^N : X^\top \left(M_0 + \sum_{k=1}^n x_k M_k \right) X \geq 0$$

of the form of the formulæ we are interested in for programs which semantics can be expressed as *LMI*s:

$$\bigwedge_{i=1}^N \sigma_i(x_0, x) \geq_i 0 = \bigwedge_{i=1}^N (x_0 \ x \ 1) M_i (x_0 \ x \ 1)^\top \geq_i 0$$



Floyd's method for termination of while B do C

Find $\mathbb{R}/\mathbb{Q}/\mathbb{Z}$ -valued unknown parameters a , such that:

- Nonnegative: $\exists \lambda \in [1, N] \mapsto \mathbb{R}^{+ i} :$

$$\forall x_0, x : r_a(x_0) - \sum_{i=1}^N \lambda_i (x_0 \ x \ 1) M_i (x_0 \ x \ 1)^\top \geq 0$$

- Strictly decreasing: $\exists \eta > 0 : \exists \lambda' \in [1, N] \mapsto \mathbb{R}^{+ i} :$

$$\forall x_0, x : (r_a(x_0) - r_a(x) - \eta) - \sum_{i=1}^N \lambda'_i (x_0 \ x \ 1) M_i (x_0 \ x \ 1)^\top \geq 0$$




Idea 6

Solve the convex constraints by semidefinite
programming



The simplex for linear programming



Dantzig 1948, exponential in worst case, good in practice

Polynomial Methods for Linear Programming

Ellipsoid method :


- Shor 1970 and Yudin & Nemirovskii 1975,
- polynomial in worst case Khachian 1979,
- but not good in practice

Interior point method :

- Kamarkar 1984,
- polynomial for both average and worst case, and
- good in practice (hundreds of thousands of variables)




The interior point method



Interior point method for semidefinite programming

- Nesterov & Nemirovskii 1988, good in practice (thousands of variables)



- Various path strategies e.g. “stay in the middle”

Semidefinite programming solvers

Numerous solvers available under MATLAB[®], a.o.:

- [lmiLab](#): P. Gahinet, A. Nemirovskii, A.J. Laub, M. Chilali
- [Sdplr](#): S. Burer, R. Monteiro, C. Choi
- [Sdpt3](#): R. Tütüncü, K. Toh, M. Todd
- [SeDuMi](#): J. Sturm
- [bnb](#): J. Löfberg (integer semidefinite programming)

Common interfaces to these solvers, a.o.:

- [Yalmip](#): J. Löfberg

Sometime need some help (feasibility radius, shift,...)

Linear program: termination of Euclidean division

```
» clear all
% linear inequalities
%
%      y0 q0 r0
Ai = [ 0  0  0; 0  0  0;
       0  0  0];
%
%      y  q  r
Ai_ = [ 1  0  0; % y - 1 >= 0
        0  1  0; % q - 1 >= 0
        0  0  1]; % r >= 0
bi = [-1; -1; 0];
%
% linear equalities
%
%      y0 q0 r0
Ae = [ 0 -1  0; % -q0 + q -1 = 0
       -1  0  0; % -y0 + y = 0
       0  0 -1]; % -r0 + y + r = 0
%
%      y  q  r
Ae_ = [ 0  1  0; 1  0  0;
        1  0  1];
be = [-1; 0; 0];
```

Iterated forward/backward polyhedral analysis:

```
{y>=1}
q := 0;
{q=0,y>=1}
r := x;
{x=r,q=0,y>=1}
while (y <= r) do
  {y<=r,q>=0}
  r := r - y;
  {r>=0,q>=0}
  q := q + 1
  {r>=0,q>=1}
od
{q>=0,y>=r+1}
```



```


» [N Mk(:,:, :)]=linToMk(Ai, Ai_, bi);
» [M Mk(:,:, N+1:N+M)]=linToMk(Ae, Ae_, be);
» [v0,v]=variables('y','q','r');
» display_Mk(Mk, N, v0, v);
+1.y -1 >= 0
+1.q -1 >= 0
+1.r >= 0
-1.q0 +1.q -1 = 0
-1.y0 +1.y = 0
-1.r0 +1.y +1.r = 0
» [diagnostic,R] = termination(v0, v, Mk, N, 'integer', 'quadratic');
» disp(diagnostic)
    termination (bnb)
» intrank(R, v)
r(y,q,r) = -2.y +2.q +6.r

```

Floyd's proposal $r(x, y, q, r) = x - q$ is more intuitive but requires to discover the nonlinear loop invariant $x = r + qy$.



Imposing a feasibility radius



Quadratic program: termination of factorial

Program:

```
n := 0;  
f := 1;  
while (f <= N) do  
    n := n + 1;  
    f := n * f  
od
```

LMI semantics:

$$\begin{aligned} -1.f_0 + 1.N_0 &\geq 0 \\ +1.n_0 &\geq 0 \\ +1.f_0 - 1 &\geq 0 \\ -1.n_0 + 1.n - 1 &= 0 \\ +1.N_0 - 1.N &= 0 \\ -1.f_0.n + 1.f &= 0 \end{aligned}$$

$$\begin{aligned} r(n, f, N) &= -9.993455e-01.n + 4.346533e-04.f \\ &\quad + 2.689218e+02.N + 8.744670e+02 \end{aligned}$$




Idea 7

Convex abstraction of non-convex constraints



Semidefinite programming relaxation for polynomial programs

```
eps = 1.0e-9;  
while (0 <= a) & (a <= 1 - eps)  
    & (eps <= x) & (x <= 1) do  
    x := a*x*(1-x)  
od
```



Write the verification conditions in polynomial form, use SOS solver to relax in semidefinite programming form.

SOSTool+SeDuMi:

$$r(x) = 1.222356e-13 \cdot x + 1.406392e+00$$



Considering More General Forms of Programs



Handling disjunctive loop tests and tests in loop body

- By case analysis
- and “conditional Lagrangian relaxation” (Lagrangian relaxation in each of the cases)



Loop body with tests

```
while (x < y) do
    if (i >= 0) then
        x := x+i+1
    else
        y := y+i
    fi
od
```

→ case analysis: $\begin{cases} i \geq 0 \\ i < 0 \end{cases}$

lmlab:

```
r(i,x,y) = -2.252791e-09.i -4.355697e+07.x +4.355697e+07.y
+5.502903e+08
```



Quadratic termination of linear loop

```
{n>=0}  
i := n; j := n;  
while (i <> 0) do  
    if (j > 0) then  
        j := j - 1  
    else  
        j := n; i := i - 1  
    fi  
od
```


← termination precondition
determined by iterated for-
ward/backward polyhedral
analysis



`sdplr` (with feasibility radius of $1.0e+3$):

```
r(n,i,j) = +7.024176e-04.n^2 +4.394909e-05.n.i ...  
          -2.809222e-03.n.j +1.533829e-02.n ...  
          +1.569773e-03.i^2 +7.077127e-05.i.j ...  
          +3.093629e+01.i -7.021870e-04.j^2 ...  
          +9.940151e-01.j +4.237694e+00
```

Successive values of
 $r(n, i, j)$ for $n = 10$ on
loop entry



Handling nested loops

- by induction on the loop depth
- use an iterated forward/backward symbolic analysis to get a necessary termination precondition
- use a forward symbolic symbolic analysis to get the semantics of a loop body
- use Lagrangian relaxation and semidefinite programming to get the ranking function



Example of termination of nested loops: Bubblesort inner loop

```
...
+1.i' -1 >= 0
+1.j' -1 >= 0
+1.n0' -1.i' >= 0
-1.j +1.j' -1 = 0
-1.i +1.i' = 0
-1.n +1.n0' = 0
+1.n0 -1.n0' = 0
+1.n0' -1.n' = 0
...
```

Iterated forward/backward polyhedral analysis
followed by forward analysis of the body:

```
assume (n0 = n & j >= 0 & i >= 1 & n0 >= i & j <> i);
{n0=n,i>=1,j>=0,n0>=i}
assume (n01 = n0 & n1 = n & i1 = i & j1 = j);
{j=j1,i=i1,n0=n1,n0=n01,n0=n,i>=1,j>=0,n0>=i}
j := j + 1
{j=j1+1,i=i1,n0=n1,n0=n01,n0=n,i>=1,j>=1,n0>=i}
```

termination (lmilab)

```
r(n0,n,i,j) = +434297566.n0 +226687644.n -72551842.i
-2.j +2147483647
```



Example of termination of nested loops: Bubblesort outer loop

```
...  
+1.i' +1 >= 0  
+1.n0' -1.i' -1 >= 0  
+1.i' -1.j' +1 = 0  
-1.i +1.i' +1 = 0  
-1.n +1.n0' = 0  
+1.n0 -1.n0' = 0  
+1.n0' -1.n' = 0  
...
```

Iterated forward/backward polyhedral analysis
followed by forward analysis of the body:

```
assume (n0=n & i>=0 & n>=i & i <> 0);  
{n0=n, i>=0, n0>=i}  
assume (n01=n0 & n1=n & i1=i & j1=j);  
{j1=j, i=i1, n0=n1, n0=n01, n0=n, i>=0, n0>=i}  
j := 0;  
while (j <> i) do  
    j := j + 1  
od;  
i := i - 1  
{i+1=j, i+1=i1, n0=n1, n0=n01, n0=n, i+1>=0, n0>=i+1}
```

termination (lmilab)

r(n0,n,i,j) = +24348786.n0 +16834142.n +100314562.i +65646865



Handling nondeterminacy

- By case analysis
- Same for concurrency by interleaving
- Same with fairness by nondeterministic interleaving with encoding of an explicit bounded round-robin scheduler (with unknown bound)



Termination of a concurrent program

```
[| 1: while [x+2 < y] do           while (x+2 < y) do
    2:     [x := x + 1]             if ?=0 then
        od                         x := x + 1
    3:                               else if ?=0 then
||                               y := y - 1
  1: while [x+2 < y] do           →   else
  2:     [y := y - 1]             x := x + 1;
        od                         y := y - 1
  3:                               fi fi
| ]                                od
```

penbmi: $r(x, y) = 2.537395e+00 \cdot x + -2.537395e+00 \cdot y + -2.046610e-01$



Termination of a fair parallel program

```
[[ while [(x>0) | (y>0)] do x := x - 1] od ||  
  while [(x>0) | (y>0)] do y := y - 1] od ]]
```

interleaving
+ scheduler
→

{m>=1} ← termination precondition determined by iterated
forward/backward polyhedral analysis

```
t := ?;  
assume (0 <= t & t <= 1);  
s := ?;  
assume ((1 <= s) & (s <= m));  
while ((x > 0) | (y > 0)) do  
  if (t = 1) then  
    x := x - 1  
  else  
    y := y - 1  
  fi;  
  s := s - 1;
```

```
if (s = 0) then  
  if (t = 1) then  
    t := 0  
  else  
    t := 1  
  fi;  
  s := ?;  
  assume ((1 <= s) & (s <= m))  
else  
  skip  
fi  
od;;
```

penbmi: r(x,y,m,s,t) = +1.000468e+00.x +1.000611e+00.y
+2.855769e-02.m -3.929197e-07.s +6.588027e-06.t +9.998392e+03



Relaxed Parametric Invariance Proof Method



Floyd's method for invariance

Given a loop precondition P , find an unknown loop invariant I such that:

- The invariant is *initial*:

$$\forall x : P(x) \Rightarrow I(x)$$

- The invariant is *inductive*:



Abstraction

- Express loop semantics as a conjunction of LMI constraints (by relaxation for polynomial semantics)
- Eliminate the conjunction and implication by Lagrangian relaxation
- Fix the form of the unknown invariant by parametric abstraction

... we get ...



Floyd's method for numerical programs

Find $\mathbb{R}/\mathbb{Q}/\mathbb{Z}$ -valued unknown parameters a , such that:

- The invariant is *initial*: $\exists \mu \in \mathbb{R}^+$:

$$\forall x : I_a(x) - \mu.P(x) \geq 0$$

- The invariant is *inductive*: $\exists \lambda \in [0, N] \rightarrow \mathbb{R}^+$:

$$\forall x, x' : I_a(x') - \lambda_0.I_a(x) - \sum_{k=1}^N \lambda_k.\sigma_k(x, x') \geq 0$$

$\uparrow \quad \uparrow \quad \quad \quad k=1$

bilinear in λ_0 and a



Idea 8

Solve the bilinear matrix inequality (BMI) by
semidefinite programming



Bilinear matrix inequality (BMI) solvers

$$\exists x \in \mathbb{R}^n : \bigwedge_{i=1}^m \left(M_0^i + \sum_{k=1}^n x_k M_k^i + \sum_{k=1}^n \sum_{\ell=1}^n x_k x_{\ell} N_{k\ell}^i \succcurlyeq 0 \right)$$

Minimizing $x^\top Qx + cx]$

Two solvers available under MATLAB[®]:

- PenBMI: M. Kočvara, M. Stingl
- bmibnb: J. Löfberg

Common interfaces to these solvers:

- Yalmip: J. Löfberg



Example: linear invariant

Program:

```
i := 2; j := 0;  
while (??) do  
    if (??) then  
        i := i + 4  
    else  
        i := i + 2;  
        j := j + 1  
    fi  
od;
```

– Invariant:

$$+2.14678e-12*i -3.12793e-10*j +0.486712 \geq 0$$

- Less natural than $i - 2j - 2 \geq 0$
- Alternative:
 - Determine parameters (a) by other methods (e.g. random interpretation)
 - Use BMI solvers to *check* for invariance



Conclusion



Constraint resolution failure

- infeasibility of the constraints does not mean “non termination” or “non invariance” but simply **failure**
- inherent to **abstraction!**



Numerical errors

- LMI/BMI solvers do numerical computations with **rounding errors**, shifts, etc
- ranking function is subject to **numerical errors**
- the hard point is to **discover** a candidate for the ranking function
- much less difficult, when the ranking function is known, to **re-check** for satisfaction (e.g. by static analysis)
- **not very satisfactory for invariance** (checking only ???)



Related anterior work

- Linear case (Farkas lemma):
 - Invariants: Sankaranarayanan, Spina, Manna (CAV'03, SAS'04, heuristic solver)
 - Termination: Podelski & Rybalchenko (VMCAI'03, Lagrange coefficients eliminated by hand to reduce to linear programming so no disjunctions, no tests, etc)
 - Parallelization & scheduling: Feautrier, easily generalizable to nonlinear case




Related posterior work

- Termination using Lyapunov functions: Rozbehani, Feron & Megrestki (HSCC 2005)



Seminal work

- LMI case, Lyapunov 1890,
“an invariant set of a differential equation is stable in the sense that it attracts all solutions if one can find a function that is bounded from below and decreases along all solutions outside the invariant set”.



THE END, THANK YOU

More details and references in the VMCAI'05 paper.



Sep. 6, 2006

— 99 —

© P. Cousot



ANNEX

- Main steps in a typical soundness/completeness proof
- SOS relaxation principle



Main steps in a typical soundness/completeness proof

$$\begin{aligned} & \exists r : \forall x, x' : \llbracket B \mid C \rrbracket (x \ x') \Rightarrow r(x, x') \geq 0 \\ \iff & \exists r : \forall x, x' : \bigwedge_{k=1}^N \sigma_k(x, x') \geq 0 \Rightarrow r(x, x') \geq 0 \\ \Leftarrow & \quad \text{(Lagrangian relaxation } (= \Rightarrow \text{ if lossless})\} \\ & \exists r : \exists \lambda \in \llbracket 1, N \rrbracket \mapsto \mathbb{R}_* : \forall x, x' \in \mathbb{D}^n : r(x, x') - \\ & \quad \sum_{k=1}^N \lambda_k \sigma_k(x \ x') \geq 0 \end{aligned}$$



\Leftarrow

{Semantics abstracted in LMI form (\Rightarrow if exact abstraction)}

$$\exists r : \exists \lambda \in [1, N] \mapsto \mathbb{R}_* : \forall x, x' \in \mathbb{D}^n : r(x, x') - \sum_{k=1}^N \lambda_k (x x' 1) M_k (x x' 1)^\top \geq 0$$

\iff

{Choose form of $r(x, x') = (x x' 1) M_0 (x x' 1)^\top$ }

\iff

$$\exists M_0 : \exists \lambda \in [1, N] \mapsto \mathbb{R}_* : \forall x, x' \in \mathbb{D}^n : (x x' 1) M_0 (x x' 1)^\top - \sum_{k=1}^N \lambda_k (x x' 1) M_k (x x' 1)^\top \geq 0$$



$\iff \exists M_0 : \exists \lambda \in [1, N] \mapsto \mathbb{R}_* : \forall x, x' \in \mathbb{D}^{(n \times 1)} :$

$$\begin{bmatrix} x \\ x' \\ 1 \end{bmatrix}^\top \left(M_0 - \sum_{k=1}^N \lambda_k M_k \right) \begin{bmatrix} x \\ x' \\ 1 \end{bmatrix} \geq 0$$

\iff if $(x \ 1) A (x \ 1)^\top \geq 0$ for all x , this is the same as $(y \ t) A (y \ t)^\top \geq 0$ for all y and all $t \neq 0$ (multiply the original inequality by t^2 and call $xt = y$). Since the latter inequality holds true for all x and all $t \neq 0$, by continuity it holds true for all x, t , that is, the original inequality is equivalent to **positive semidefiniteness** of A)



$$\exists M_0 : \exists \lambda \in [1, N] \mapsto \mathbb{R}_* : \left(M_0 - \sum_{k=1}^N \lambda_k M_k \right) \succcurlyeq 0$$

LMI solver provides M_0 (and λ)

SOS Relaxation Principle

- Show $\forall x : p(x) \geq 0$ by $\forall x : p(x) = \sum_{i=1}^k q_i(x)^2$
- Hibert's 17th problem (sum of squares)
- Undecidable (but for monovariable or low degrees)
- Look for an approximation (relaxation) by semidefinite programming



General relaxation/approximation idea

- Write the polynomials in quadratic form with monomials as variables: $p(x, y, \dots) = z^\top Q z$ where $Q \succeq 0$ is a semidefinite positive matrix of unknowns and $z = [\dots x^2, xy, y^2, \dots x, y, \dots 1]$ is a monomial basis
- If such a Q does exist then $p(x, y, \dots)$ is a sum of squares⁵
- The equality $p(x, y, \dots) = z^\top Q z$ yields LMI contrains on the unkown Q : $z^\top M(Q)z \succeq 0$

⁵ Since $Q \succeq 0$, Q has a Cholesky decomposition L which is an upper triangular matrix L such that $Q = L^\top L$. It follows that $p(x) = z^\top Q z = z^\top L^\top L z = (Lz)^\top L z = [L_{i,:} \cdot z]^\top [L_{i,:} \cdot z] = \sum_i (L_{i,:} \cdot z)^2$ (where \cdot is the vector dot product $x \cdot y = \sum_i x_i y_i$), proving that $p(x)$ is a sum of squares whence $\forall x : p(x) \geq 0$, which eliminates the universal quantification on x .



- Instead of quantifying over monomials values x, y , replace the monomial basis z by auxiliary variables X (loosing relationships between values of monomials)
- To find such a $Q \succcurlyeq 0$, check for semidefinite positivity $\exists Q : \forall X : X^\top M(Q)X \geq 0$ i.e. $\exists Q : M(Q) \succeq 0$ with LMI solver
- Implement with [SOSTools](#) under MATLAB® of Prajna, Papachristodoulou, Seiler and Parrilo
- Nonlinear cost since the monomial basis has size $\binom{n+m}{m}$ for multivariate polynomials of degree n with m variables

